



**EL-OBOUR**  
شركة العبور لإنتاج الورق ش.م.م  
El-Obour for Paper Production

<b>Product:</b>	Testliner (3) 125 GSM
-----------------	-----------------------

Test Type	Units	Average	Tolerance
Grade	GSM	125	±5%
Thickness	mm	0.25	±5%
Bursting	kPa	260	±5%
Moisture	%	7	±1%
CoBB	g/60sec.	40	±5%
R.C.T (C.D)	kN/m	1.3	±5%
R.C.T (M.D)	kN/m	0.9	±5%
Tensile (C.D)	kgf/15mm	3.5	±5%
Tensile (M.D)	kgf/15mm	7.5	±5%

<b>Core:</b>	10 cm is the standard size.
<b>Reel Width:</b>	Minimum width is 50 cm. Maximum width is 200 cm. The trimmed width of the paper machines is 3.5 m.
<b>Marking:</b>	Printed on the core. The label is on the belly.
<b>Reel Diameter:</b>	120-140 cm.
<b>Reel Wrapping:</b>	Paper end is both glued and taped.



Industrial Zone - El-Obour City



37 Ismail Ramzy St, Heliopolis, Cairo, Egypt



info@obourforpaper.com



(+202) 26440085 - 26440086



(+202) 26397556



www.obourforpaper.com